

### Camera Module Comparison Chart

FEATURE	ANALOG	HD	COMMENTS
OSD-On Screen Display HD Only		X	<a href="#">Settings</a>
Resolution	800 TVL	1080p/720p	
Effective Pixels	976 x 582	1080x1920 720 x 1920	
Frame Rate [fps] HD-SDI ( up to 150' cable)		60 1080 / 30	
Frame Rate HD-AHD		1080p/30	Cable up to 1000
Color / B&W	X *	X	* Specified at time of order
NTSC or PAL	X **	X	** Factory Set
Fixed Focus	X	X	
Viewed at Surface	X	X	
50 – 100' Depth	X	X	HD-SDI* Custom Request
200 – 1000' Depth	X	X	HD-AHD
50 – 1000' Depth	X		Analog
1000# Pull Cable	X	X	Sea-Serpent Cable
Armored Cable Opt.	X		600' /1500# pull
Lexan Lens	X	X	
Degree View Angle	72-77	72-77	
Standard Lens	4.2mm	4.2mm	Custom Available
Lux Color	Not Specified		1
Lux B&W		0.001	0.5
Gas Filled Chamber	X	X	Stops Condensation
Camera Voltage 12V	X	X	< 500'
110-240 Adapter	X	X	
Voltage Smoothing	X	X	
1000' Depth Rated	X	X	
Internal /External Light Option	X	X	

OSD - On Screen Display - HD camera settings can be changed/adjusted from the surface.

All specifications are based on NTSC and are slightly less under PAL standards.

Adapters may be required (included) at higher voltage for longer length cables.

\* Factory configured as either B&W or Color / \*\* Must be ordered as NTSC or PAL